

Model Information



■ Features

- AMD Geode LX 800, 500MHz without fan, inkl. 512MB DDR SoDIMM, VGA on board
- 1 x LAN / 4 x USB 2.0
- 2x RS232
- Compact Flash Adapter
- Power Supply AC-DC 24W or DC 12-24V terminal block
- Dimensions 123.0mm x 120.0mm x 44mm
- HDD Space
- Keyboard/Mouse connector

[Contact Online...](#)

EmRunner 5202 DIN RAIL

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [System](#) | [Storage](#) | [Chassis](#) | [Power Requirements](#) | [Power Consumption](#) | [Environment](#) | [Ordering Information](#) | [optional](#) |

■ More Pictures



Klick on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The really small and robust embedded system! Fan less, Low Power Consumption, Professional construction inside!

■ System

CPU AMD Geode LX-800 Processor
(128KB cache, 500 MHz)

Chipset: AMD Geode CS5536

Memory 512MB DDR (1GB max.)
1x 200-Pin SoDIMM

I/O Interface Front

- 1x LAN ports (Realtek RTL8100C Chipset)
- 2x USB 2.0 ports
- 1x DB15 VGA port
- 2x DB9 serial port RS232
- 1x PS/2 for keyboard/mouse
- 1x earphone-out
- 1x mic-in

I/O Interface Up

- AT power on/off switch and reset button
- HDD access/power/LAN status LEDs
- 12-24V DC power input

[>Back to top](#)

■ Storage

HDD/SSD

1x 2.5" PATA HDD drive bay

Flash

1x internal CF socket

[>Back to top](#)

■ Chassis

Construction

Aluminium chassis with fanless design

Dimensions

44 x 120 x 123 mm

[>Back to top](#)

■ Power Requirements

DC

12V - 24V DC on-board power support

[>Back to top](#)

■ Power Consumption

with power supply

ca. 15W

average system alone

ca. 6.9W

[>Back to top](#)

■ Environment

Operating Temp.

0°C - 50°C

Storage Temp.

-20°C – 80°C

[>Back to top](#)

■ Ordering Information

Part number

204
EmRunner 5202

Packing list

EmRunner 5202 DIN RAIL System
CD, English documentation
2 x L-type universal fixers with 4 screws
1 x 44-pin flat cable and 4 screws for fixing and connecting hdd
1 x 2-pin apertable terminal block
1 x PS-2 Y cable for keyboard/mouse

[>Back to top](#)

■ optional

Memory

DDR up to 1GB

Mass Storage device

2.5 HDD PATA
Compact Flash Card

[>Back to top](#)

EmRunner 5202 DIN RAIL

[>Back](#)

